



Shower Pumps

Performance Shower Pumps

Installation

Servicing

Repairs

Pumps

Pump controls

Water Treatment

Private Water Supplies

Borehole Drilling

Sewage Treatment

Storage tanks

Drainage Products

Pipes

Hoses

Fittings

Agricultural Supplies

Grundfos Performance Shower Pumps New Range

Grundfos has a reputation for high quality & reliability in the pump industry. We are pleased to announce that we are stocking the Grundfos Shower Pump range and offer these to you at very competitive prices.

Amazon: Premium Heavy Duty Brass Pumps



The Brass Pump range is undoubtedly the 'Rolls Royce' of Grundfos shower pumps, designed and manufactured to the highest of standards.

With brass impellers and machined brass stampings these pumps can be genuinely described as 'Heavy Duty', and each mode offers high performance and durability.

These continuously rated regenerative pumps are suited to domestic, commercial or light industrial use. Products within this range are fitted with long-life silicon carbide seals and anti-vibration feet keep the operating noise to a minimum.

Range	Bar	Code
Twin Impeller	2.0	STP-2.0 B
Single Impeller	3.0	SSP-3.0 B
Twin Impeller	3.0	STP-3.0 B

All brass pumps are supplied with stainless steel flexible hoses, and are covered by a comprehensive 2 years warranty. A brass pump will transform any compatible shower system into a really enjoyable and invigorating power shower.

The installation of a Grundfos Surrey flange is recommended for pumps up to 3 bar pressure.

Amazon: Universal Brass Pump

A twin or single brass impeller shower pump, which is WRAS approved.

These continuously rated regenerative pumps are suited to domestic, commercial or light industrial use. Products within this range are fitted with long-life silicon carbide seals and anti-vibration feet keep the operating noise to a minimum.

All brass pumps are supplied with stainless steel flexible hoses, and are covered by a comprehensive 2 years warranty. A brass pump will transform any compatible shower system into a really enjoyable and invigorating power shower.



Amazon Extra: Universal Single Ended Pumps



This pump is ideal for boosting water pressure in domestic or light commercial pressurised hot and cold water systems, in properties with up to four bathrooms with standard fittings, or en-suite, and cloakroom plus normal household appliances.

This pump is also ideal for use in such places as sports clubs, leisure centres and schools wanted to boost multiple shower heads when installed after the shower valve or mixer.

The installation should be to either a pressurised system or from an open vented hot or cold water system, where the pump is positioned below the cold water cistern.

The Amazon Extra range of pumps are suitable for either positive or negative head applications.

Nile: Automatic Shower Pump

A twin impeller centrifugal shower pump, tested and approved to BSEN 60335.

This pump is fitted with long-life seals and is supplied complete with easy clean filters and high quality braided stainless steel connection hoses.

All pumps in the range, which are designed for domestic shower and bathroom applications, are covered by a comprehensive two year manufacturer's warranty.

Choose from our standard 1.5 bar or the 2 bar.

Suitable for use with 15mm or 22mm pipework.

The installation of a Grundfos Surrey flange is recommended for maximum shower pump efficiency on both.

Range	Bar	Code
Twin Impeller	1.5	STC-1.5 C
Twin Impeller	2.0	STC-2.0 C

Nile: Regenerative 240 Volt Pumps

The Nile range is the result of extensive research and development giving a high performance pump at an affordable price. An innovative design, incorporating a low-speed induction motor, gives long life and, combined with anti-vibration feet, ensures that operating noise is kept to a minimum. With automatic thermal overload protection the pump motor will cut out to prevent overheating, resetting automatically within 30-60 minutes.

The range is designed for domestic shower and bathroom applications. All models are fitted with long life carbon graphite and high density ceramic seals.

Range	Bar	Code
Single Impeller	1.5	SSR-1.5 C

The range is supplied with stainless steel flexible hoses, and covered by a comprehensive 2 years warranty. Manual negative head kits are available from Grundfos.

Amazon: Specialist Automatic Negative Head Pumps

Where the water level in the cold storage tank is below the level of the shower outlet a 'negative head' situation exists. Specialist Automatic Negative Head pumps to overcome this problem.

Manual Negative

Manually operated Negative Head Kits are also available from Grundfos for all pump ranges excluding Premier Heavy Duty Brass. To size your pump correctly to meet with your requirements, please call Filpumps on 01467 623010.

Range	Bar	Code
Twin Impeller	3.0	STN-3.0 B

Danube Universal: Twin Centrifugal Pump

This twin impeller centrifugal pump is WRAS approved and has an external transformer for ultimate safety. Unique to the UK market this pump is supplied with stainless steel braided hoses, a universal head and a two year warranty.



Range	Bar	Code
Twin Impeller	2.0	STL - 2.0 C

Danube: Single or Twin Centrifugal Pump



This single or twin impeller centrifugal pump is WRAS approved and has an external transformer for ultimate safety. Unique to the UK market this pump is supplied with stainless steel braided hoses and a two year warranty.

Range	Bar	Code
Single Impeller	1.4	SSL - 1.4 C
Twin Impeller	1.0	STL - 1.0 C
Twin Impeller	1.5	STL - 1.5 C
Twin Impeller	2.0	STL - 2.0 C

Negative Head Kit



Manual pneumatic Negative head kits are available for the Niagara range, Nile range and Danube range.

They are all supplied with Button, 7m hose and replacement terminal lid for pump.

Surrey & York Flanges


Considered an industry standard, the Surrey flange is designed to provide an independent hot water supply as well as dramatically reduce air surging, noise and temperature variations.

The Surrey flange air vent automatically purges the shower circuit preventing air accumulation in the hot water shower feed (patent applied for). The vent automatically traps and releases air, preventing back feed of aerated hot water. The installation of a Surrey flange is recommended for shower pumps up to 3 bar pressure.

15mm Surrey Flange: To suit cylinder outlet of 1" BSP female. Suited to pumps up to 1.5 bar pressure.

22mm Surrey Flange: To suit cylinder outlet of 1" BSP Female. Suited to pumps up to 3 bar pressure.

York Flange: The York flange is a modified version of the 22mm Surrey flange, with an adaptor to suit cylinders with 1" BSP Male outlets. Suited to pumps up to 3 bar pressure.





Thainstone Business Park
Inverurie
Aberdeenshire
AB51 5GT

Tel 01467 623010

Fax 01467 623011

info@filpumps.co.uk

www.filpumps.co.uk

